

# Mini Mods 2018

4 Cylinder OR 6 Cylinder NO FULL FRAME CARS

**STRIPPING:** All glass, plastic, fiberglass, and chrome moldings must be removed. Station Wagon rear floor door must be removed. No broken window in doors. No flammable materials such as carpets, upholstery or headliners can be left in the car. Cars MUST be clean and free of loose objects inside and in the trunk area. Both rear seats and insulation blanket under the hood MUST be removed. Dashboards may be removed. Bumper covers must be removed.

**BODY:** MUST look like a car. Must be safe for driver and other participants. NO V-8's. Don't be stupid and go all out, but do NOT under build and be upset. No home made cars, MUST start as a production car. 108" maximum wheel base.

**HOOD:** Hood MUST have 10"-12"hole. Secure your hood only AFTER your car passes tech inspection.

**TRUNK AND TAILGATE:** Trunk MUST be empty and free of dirt and debris.

**DOORS:** All doors MUST be securely closed.

**WINDOWS:** DO NOT cover driver's window with steel or mesh type material for safety reasons.

**BUMPERS:** No more than 8" point.

**INTERIOR:** Driver's seat and DOT approved seat belts MUST be securely mounted.

**CHASSIS:** Trailer hitches and mounting brackets MUST be removed. You may use stock or modified steering columns. You may replace or modify knuckles and/or joints in steering assembly. Reinforced tie rods are permitted.

**REAR SUSPENSION:** Bumper height maximum 22" from ground to bottom of bumper and it is strictly enforced. Coil springs may be changed but bumper height must remain 22" or less. A straight axle in rear may be used. Leaf springs permitted. (mini van style rear axle).

**ENGINE:** Engine or pulley protectors and carb protectors will be allowed. Motor may be chained to frame and motor mounts may be altered and strengthened. Carburetor must have an air filter.

**RADIATOR:** Radiator MUST be located in stock position. Radi-barrels or homemade type radiators will be allowed. Water ONLY, please flush out coolant. If you run a radiator fan you must run a hood.

**ELECTRICAL:** Batteries MUST be located inside of car on passenger's front floor, and MUST be securely mounted with a 4 point hold down on each and both MUST be covered. Batteries and boxes MUST be secured. Push button or toggle ignition and power hot wiring switches are acceptable. Solenoid, voltage regulators, coils and other electrical components may be relocated.

**TRANSMISSION:** Transmission coolers are acceptable. Cooler may be mounted inside of car but MUST be NO longer than 24" X 24" X 18", this means that the complete unit including box around cooler NOT to exceed these dimensions. ALL LINES TRAVELING INSIDE OF DRIVERS COMPARTMENT, MUST USE METAL LINES OR HIGH PRESSURE HYDRAULIC LINES, AND RUN THROUGH SOME FORM, OF ANOTHER HOSE. If it does not pass inspection you will be asked to loop it off.

**GAS TANK:** Six-gallon fuel cell highly recommended. Original gas tank MUST be removed, may NOT use original fuel tank inside car NO exceptions. Tank MUST be metal, NO plastic or stock fuel tanks will be allowed, NO exceptions. Marine style gas tanks are acceptable. NO plastic or jerry cans. Tanks MUST be securely mounted and all connections must be secure and leak-proof. Stop check valves are highly recommended. Gas tanks must be completely covered. Pump fuel only (NO Alcohol or methanol). Fuel Line rubber fuel line is highly recommended from gas tank to fuel pump. Electric Fuel pumps are acceptable but MUST have shut off switch within drivers reach and clearly marked for fire officials. NO plastic lines. Gas spillage will result in disqualification. Fuel tank protectors will be allowed.

**BRAKES:** Brakes MUST be functional in the start of every heat or feature.

**TIRES & RIMS:** Any ply, 12", 13", 14", or 15" tires are permitted. Maximum allowance of 25" tall and 7" width double tires (tire inside tire), rubber inner-liners or solid rubber tires are acceptable. NO studded tires. NO wheel weights, double rims or split rims. Valve stem guards are permitted. Full weld in centers and bead lock/rim protectors will be allowed.

**REMEMBER OFFICIAL DECISIONS ARE FINAL!**